

# PR11P-S-SAE

## PR Power Diesel Generator Specifications



Generator image used for illustration purposes only

PR Power's range of diesel generators have been designed and manufactured to meet Australian and European standards and are available for sale Australia wide.

The PR11P-S-SAE is a single phase, sound attenuated unit complete with lockable access doors and control panel. Additional accessories or modifications are also available on request.

In addition to the PR range of generators, PR Power also have available mobile lighting towers and water solution equipment Australia wide.

For more information on our range of generators and other equipment contact our office today on 1300 399 499 or visit our website at [www.prpower.com](http://www.prpower.com).

### KEY FEATURES

- Fully lockable access doors and control panel
- Super quiet, sound attenuated enclosure, to exceed industry standards
- 12v set mounted battery, with lockable isolator
- 24hr run, bunded base fuel tank (Comply to AS1940-2004 and EPA 2012 standards)
- External fill, lockable fuel cap
- Fuel contents gauge
- Emergency stop button
- Manual oil drain pump
- Central lifting point, forklift pockets and dragging lug points
- Long lasting, heavy duty powder coated finish
- Engine/alternator resiliently mounted on steel base frame

### TECHNICAL DATA

#### GENERATOR SPECIFICATIONS

Type	Synchronous
Single phase (Prime) power	10kVA/10kW
Voltage/Frequency	240V/50Hz
Amps	41A
Insulation Class	H
Protection	IP23
Alternator Brand	Brushless Leroy Somer
Alternator Model	LSA40VS2

#### ENGINE SPECIFICATIONS

Engine type	Perkins 403D-15G	
Cylinders	3	
Displacement	1.496L	
Engine speed	1500rpm	
Intake System	Naturally aspirated	
Cooling system	50°C	
Coolant Capacity	6.0L	
Oil Capacity	6.0L	
Governor	Mechanical	
Fuel type	Diesel	
Starting system	12V electric	
Fuel Consumption	100%	50%
	3.6L/h	2.0L/h

#### GENERAL SPECIFICATIONS

Sound pressure level	59.6dBA@7m (100% load)
Fuel tank capacity	100L
Controller	Deep Sea 702
Auto Engine Protection Shutdown (Deep Sea Control Panel)	<ul style="list-style-type: none"><li>▪ Auto remote</li><li>▪ Manual Start</li><li>▪ Robust digital display package</li></ul>
Generator Including Enclosure - Dimensions	
Dimensions (LxWxH)	1892 x 967 x 1350mm
Dry Weight	830kg

**Standby Rating:** These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528-3).

**Prime Rating:** These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

**Standard Reference Conditions:** Standard reference conditions 25°C (77°F) air inlet temp, 100m (328ft) A.S.L 30% relative humidity. Fuel consumption data at full load with diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, Class A2.

**Note:** kVA ratings subject to ambient temperature/altitude/site conditions. Engine kW rating may vary +/- 3%.

t. 1300 399 499

e. [sales@prpower.com](mailto:sales@prpower.com) | w. [www.prpower.com](http://www.prpower.com)

**PRPOWER**  
Performance and Reliability