


# PR1650C

## PR Power Diesel Generator Specifications



Generator image used for illustration purposes only

PR Power's range of diesel generators have been designed and manufactured to meet Australian and European standards and are available for sale Australia wide.

The PR1650C is a three phase, robust, open set generator ideally suited for mining, construction and rental applications. Additional accessories or modifications, including parallel and synchronising functions, are also available on request.

In addition to the PR range of generators, PR Power also have available mobile lighting towers and water solution equipment Australia wide.

For more information on our range of generators and other equipment contact our office today on 1300 399 499 or visit our website at [www.prpower.com](http://www.prpower.com).

### KEY FEATURES

- 24v set mounted batteries, with lockable isolator
- Emergency stop button located on either side of the unit
- Corner fittings to to ISO1161. Four point lifting
- Fork lift pockets
- Engine/alternator resiliently mounted on steel base frame

### TECHNICAL DATA

#### GENERATOR SPECIFICATIONS

Type	Synchronous
Three phase (Prime) power	1500kVA/1200kW
Voltage/Frequency	415V/50Hz
Amps	2085A
Insulation Class	H
Protection	IP23
Alternator Brand	Brushless Stamford
Alternator Model	P1734C

#### ENGINE SPECIFICATIONS

Engine type	Cummins KTA50-GS8	
Cylinders	16	
Displacement	50.3L	
Engine speed	1500rpm	
Intake System	Turbocharged/Aftercooler	
Cooling system	50°C	
Coolant Capacity	140L	
Oil Capacity	178L	
Governor	Electric	
Fuel type	Diesel	
Fuel Consumption	100%	50%
	309L/h	167L/h

#### GENERAL SPECIFICATIONS

Fuel tank capacity	1350L
Controller	Deep Sea 7420
Auto Engine Protection Shutdown (Deep Sea Control Panel)	<ul style="list-style-type: none"><li>▪ RS485 output</li><li>▪ Auto remote</li><li>▪ Manual Start</li><li>▪ Robust digital display package</li><li>▪ Easy menu navigation</li><li>▪ Advanced protection technology</li></ul>

#### Generator Dimensions

Dimensions (LxWxH)	5362 x 2110 x 2556mm
Dry Weight	9832kg

**Standby Rating:** These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528-3).

**Prime Rating:** These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

**Standard Reference Conditions:** Standard reference conditions 25°C (77°F) air inlet temp, 100m (328ft) A.S.L 30% relative humidity. Fuel consumption data at full load with diesel fuel with specific gravity of 0.85 and conforming to BS2869: 1998, Class A2.

**Note:** kVA ratings subject to ambient temperature/altitude/site conditions. Engine kW rating may vary +/- 3%.

t. 1300 399 499

e. [sales@prpower.com](mailto:sales@prpower.com) | w. [www.prpower.com](http://www.prpower.com)

**PRPOWER**  
Performance and Reliability