SIMPLE SOLAR PR-SOLAR POLE 1X 50W

The PR-SOLAR POLE LED is an easy to use solar light tower ideal for car parks, special events, rural streets, military applications and construction purposes. The PR-SOLAR POLE is automated and will switch on when the sun sets and turn itself off when the sun rises.

The PR-SOLAR POLE emits no CO₂ emissions, is completely silent and does not consume any fuel.



PRPOWER PRPOWER

High efficiency solar panel allows the unit to run with zero fuel consumption



Energy saving dim sensor which activates when movement is detected in surrounding area





KEY FEATURES

1 x 50w high efficiency Auto dim feature to save LED lamps illuminating battery, only registers when movement is detected

Strong galvanised base and powder coating for harsh environments

400m².

Simple directional light set up atop easy to use mast

approx. 400m²



Complete stand alone unit, set and forget

Lamps ignite as the sunsets Zero CO₂ emissions, no and will automatically turn of when the sun rises



No bulbs to replace on LED Lamps and they are protected by a polycarbonate lens (no glass)

sound and no fuel

vertical mast.

increasing visibility.

The tower provides 1 x 50w

high-efficiency LED lamps,

capable of illuminating around



Silent operation for reduced noise and added security



The PR-SOLAR POLE LED Lighting Tower utilises a highly efficient solar Panel mounted atop a 8.5m

The PR-SOLAR POLE LED is eqipped with an auto dim sensor which saves battery usage and efficiency of the unit. The lights will be dimmed if there is no movement within the surrounding area. If there is movement detected (e.g. a person walking past) the PR-SOLAR POLE's lights will raise to full brightness

> No replacement of ballasts and capacitors required

> Up to 46 hours of operating

time with no fuel costs and

minimal maintenance

This lighting tower is ideal for

a wide range of applications

industrial, civil works, rental and government projects.

including construction,



Compact design allows transport of up to 24 units simultaneously

TECHNICAL DATA

LIGHTING & MAST	
Type of light	1 x 50w LED
Light output	400m ²
Sensor	Auto Dim
Maximum mast height	8.5m
Mast lifting system	Manual
Electrical protection rating	IP65
Maximum wind speed	80km/h
Batteries & Solar Panel	
Solar Panel Power	130w
Battery Type	Lithium
Batteries Number	1
Power Battery Pack	656 wh
Run Time (Full Brightness)	11.5 hours
Run Time (Dimmed)	46 hours
Noise rating	No Noise, O dBA
DIMENSIONS, WEIGHT AND FEATURES	
Units Per Truck	24
Min/Max (LxWxH)	1500x600x2360/ 1500x600x5500mm
Dry weight	400kg

PROWER 1300 399 499

sales@prpower.com www.prpower.com