

PRPOWER

LED TECHNOLOGY

2400 sqm
Illuminated area

Self sufficient solar powered unit



Solar Line



Operation:
solar panel 4x360W
batteries 8x24 Vdc 800Ah

X-SOLAR

4x100W LED - 8m

T-ZEROPRO

X-SOLAR

4x100W LED - 8m

T-ZERO^{PRO}**FEATURES**

- Multi-directionally adjustable and tiltable floodlights
- 7 sections hydraulic vertical tower 8m, 340° rotatable
- Equipped with an Automatic Mast Operating Safety System (AMOSS) for added safety.
- Galvanized metalworks
- 80 µm powder coating
- Forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- **Central lifting eye**
 - Certified wind stability up to 80 km/h
 - 4 height adjustable stabilizers + front jockey wheel
 - On board levels for guidance during stabilization
- **No.8 batteries AGM, Battery Pack 24Vdc 800Ah**
 - EU Homologated Road-tow trailer
 - VICTRON controller for Tracking and Telematics e remote management

ZERO
emissions**RENEWABLE**
source of
energy**ZERO**
fuel costs**SILENT**
running**4**
extendable solar panels**2400** sqm
illuminated area**4** units per truck

Dimensions & weight	Dimensions min (mm)		Dimensions max(mm)		Total weight (kg)	
	4180x2090x2650 (LxWxH)		4180x4150x8000 (LxWxH)		1595	
Floodlights	Type	Power (each)	Floodlights number	IP level	Illuminated area (sqm)	
	Led	100W	4	65	2400	
Mast	Lifting method	Max Height	Max Wind Speed	Rotation		
	Hydraulic	8m	80 km/h	340°		
Batteries	Type	Batteries number	Power Battery pack	Expected battery cycle		
	AGM	8	24 Vdc 800 Ah	500		
Solar panel	Power (each)	Type	Solar panel deployment		Solar charge control	
	4x400 W	Victron	manual		MPPT 150/60	