

## T-ZERO<sup>PRO</sup>

### POWER & INNOVATION



Kubota



1500 RPM




WATER cooled



DIESEL



SINGLE phase



HYBRID technology



LITHIUM battery

**STAGE 5**  
CERTIFIED



#### MGTP 5000/5 TH LITHIUM 1P

Code **RP32-6MS7**

#### Features

Outlet socket	16A - 230V 32A - 230V
Inlet plug	32A - 230V
Inverter	1 x 48V/5000VA
Battery charger	1.4kW

#### Alternator

Model	Zanardi
Rated output	8kVA
Frequency	50Hz
Voltage	230V
Insulation class	H
Degree of Protection	IP23

#### Engine

Model	KUBOTA D1105
Fuel	Diesel
Engine speed	1500rpm
Noise level at 7mt	60dBA
Emissions regulations	STAGE 5

#### Consumption only engine mode

Tank capacity	200lt
Fuel consumption - Running time	3,44 l/h - 58,1 hrs

#### Lithium Batteries

Battery	12,8V - 100Ah
Batteries number	4
Battery Pack	51,2VDC-5.1kWh
Expected battery cycle	2500 - 80% DOD

#### Dimensions & Weight

Dimension	1700 x 1066 x 1450 mm
Weight	800Kg

#### ON BOARD CONTROL PANEL EQUIPPED WITH:

DSE 3110	Fuel level monitor
ON/OFF switch	Fuel reserve signal lamp
Earth leakage circuit breaker	Battery level indicator
Circuit breaker	Voltage indicator
Emergency stop	

#### Distribution Panel

1x32A-230V EEC inlet plug for battery charging
1x32A-230V EEC outlet socket
1x16A-230V EEC outlet socket

#### Standard Features

Automatic battery switch
Sound proof canopy
Exhaust gas silencer
Built in fuel tank
Bunded tank
Forklift pocket
Central lifting eye
Heavy bump stoppers
3 ways valve for external fuel tank connection

#### Continuous Inverter Output Power

5000VA

#### Overload (0,5 sec)

12500VA

#### Running Time with Constant Load from Batteries

1000W	4.1h
2000W	2.0h
4000W	1.0h

#### Recharging time - Power requested

2.7h	2.9kW
Max Loading during recharging time	3.5kW

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.